










Ball check valves Nozzle strainers

Ball check valves, nozzle strainers	Opening pressure	Mesh size	L [mm]	D [mm]	Material	Filter area (without gasket)	Ordering no.
Ball check valves* 	0.5 bar	25 M ■ red	21.5	14.8	POM	628 mm ²	065.266.56.00
	0.5 bar	60 M ■ blue	21.5	14.8	POM	628 mm ²	065.265.56.00
	0.5 bar	25 M	21	14.8	Brass	430 mm ²	065.261.30.00
	0.5 bar	60 M	21	14.8	Brass	430 mm ²	065.260.30.00
	2.5 bar	25 M ■ red	21.5	14.8	POM	628 mm ²	065.266.56.02
	2.5 bar	60 M ■ blue	21.5	14.8	POM	628 mm ²	065.265.56.02
Ball check valve (excl. strainers) 	0.5 bar	-	18.5	14.8	POM	-	065.266.56.01
Nozzle strainer* 	-	25 M ■ red	21.5	14.8	POM	628 mm ²	065.256.56.00
	-	60 M ■ blue	21.5	14.8	POM	628 mm ²	065.257.56.00
	-	80 M ■ yellow	21.5	14.8	POM	430 mm ²	A.424.310.5
Slotted strainer 	-	25 M ■ red	21.0	14.8	POM	430 mm ²	095.009.56.13.43
Cup strainer 	-	25 M	8.5	14.8	Cu/Monel	184 mm ²	065.252.26.00
	-	25 M ■ red	8.5	14.8	PA, Monel	184 mm ²	200.029.26.00.03
	-	60 M ■ blue	8.5	14.8	PA, stainless steel	184 mm ²	200.029.1C.01.03
Nozzle strainer with integrated seal for TWISTLOC 	-	25 M ■ red	19.2	18.0	POM, Santoprene	628 mm ²	065.269.7J
	-	60 M ■ blue	19.2	18.0	POM, Santoprene	628 mm ²	065.268.7J
Nozzle strainer with integrated seal for MULTIJET 	-	60 M ■ blue	19.2	18.8	POM, Santoprene	628 mm ²	065.268.7J.10

* Please note: If applicable we deliver the strainers and ball check valves in the colour coding according to ISO 19732:2007 (see page 6).

