Cluster solid stream nozzles for air or saturated steam Series 540/541




Features:

- Powerful round jet through 40 individual bore holes
- Delivery of media at an angle of approx. 240°
- Suitable for use in difficult conditions
- Suitable for immersion in liquid media

Applications:

- Injection of steam into liquids
- Injection of compressed air into bulk goods
- Injection of gas (acid and neutralization baths)





0		Weight			
G	L ₁	L ₂	ØD	Hex	[g]
1/2 BSPP	45.0	15.0	26.0	27	100.0

Spray angle	Ordering no.		Bore diameter B	V₀ air [m³/h]			M saturated steam [kg/h]				
angle	Туре	Mat. no.	no. [mm]					in Saturated Steam [Kg/n]			
		16		p [bar]				p [bar]			
		Stainless steel 303		1.0	2.0	3.0	5.0	1.0	2.0	3.0	5.0
Approx.	540.909	•	0.80	22.80	34.20	45.50	68.30	18.10	26.90	35.50	52.70
240°	540.989	•	1.00	35.50	53.30	71.00	106.50	28.20	41.70	55.10	81.70
	541.109	•	1.50	83.30	124.90	166.50	249.80	66.00	97.70	129.20	191.60
	541.189	•	2.00	129.70	194.50	259.30	389.00	103.00	152.60	201.70	299.10
	541.239		2.30	167.20	250.80	334.30	501.50	133.20	197.30	260.80	386.60



Assembly accessories can be found in Chapter 9 "Accessories".

