


# Rotating cleaning nozzle PicoWhirly Series 500.234



## Features:

- Cleaning with rotating solid jet
- Compact design for confined spaces
- Suitable for very high temperatures
- Full stainless steel design



Series 500,234

Male thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---

**Cleaning efficiency class**  
2

**Max. temperature**  
200°C

**Installation**  
Operation in every direction is possible

**Bearing**  
Kolsterised slide bearing

**Material**  
Stainless steel 316L

**Recommended operating pressure**  
3 bar

**Filtration**  
Line strainer with a mesh size of 0.3 mm/50 mesh

**Function video**  
[www.lechler.com/picowhirly](http://www.lechler.com/picowhirly)  
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section $\varnothing$ [mm]	$\dot{V}$ water [l/min]					Max. tank diameter [m]
			$p$ [bar] ( $p_{max} = 5$ bar)					
			1.0	2.0	3.0	5.0	at 40 psi [US gal/min]	
300° 	<b>500.234.G9.00</b>	1.8	5.7	8.0	<b>9.8</b>	12.7	2.5	0.9

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only. The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.